


# Blanket & Fluid Warmers

We offer a large variety of features and options for your convenience!

Future Health Concepts, Inc. offers a variety of Blanket and Fluid Warming Cabinets in both standard and custom sizes to meet individual requirements. As with all of our products, warming cabinets undergo stringent testing procedures during the manufacturing process to assure a long life, the highest quality and accurate temperature settings. We offer standard sizes along with custom sizes to meet specific requirements.

## Standard Features:

- Stainless steel or glass door
- Data logging of real time & temp w/ USB retrieval
- Keyed temperature lock out
- Push button digital operation
- Large dual digital displays
- Displays actual temperature and set point at all times
- Separate digitally controlled heating chambers
- Rapid warm time (2-6 hours depending on load)
- Uniform heating
- Fully insulated
- Audible & visual over-temp alarm
- UL/CUL approved
- FDA registered
- OSHPD pre-approved



Standard keyed temperature lockout



Optional door lock

## Options:

- Mobile base or cart
- 18" depth
- Full recess
- Pass through chamber
- Left hand door hinge
- Keyed door lock
- Seismic brackets
- 220/240 V, 50/60HZ
- Custom sizes
- Solution baskets
- Touch-screen



FHCSWC1824-B-G

(Shown w/ optional s/s solution baskets)

# Blanket & Fluid Warmers

All blanket warmers can be customized to fit your specifications!

**NEW!**

## The Industry's First Touch Screen Warmers



FHCDWC-TS-36G

(Shown w/ optional mobile base)



Alarm notifications via email and text messaging



Temperature trending in chart format



Smart phone app

#	A	B	C	D	E	F
1	Date	Time	Device Manager	Upper Temp	Lower Temp	
2	8/29/2012	13:23:52		90	85	
3	8/29/2012	13:24:52		92	85	
4	8/29/2012	13:25:52		95	85	
5	8/29/2012	13:26:52		102	85	
6	8/29/2012	13:27:52		106	87	
7	8/29/2012	13:28:52		109	90	
8	8/29/2012	13:29:52		110	92	
9	8/29/2012	13:30:52		111	95	
10	8/29/2012	13:31:52		110	99	
11	8/29/2012	13:32:52		110	102	
12	8/29/2012	13:33:52		110	105	
13	8/29/2012	13:34:52		110	109	
14	8/29/2012	13:35:52		110	115	
15	8/29/2012	13:36:52		110	118	
16	8/29/2012	13:37:52		110	122	
17	8/29/2012	13:38:52		110	125	
18	8/29/2012	13:39:52		110	127	
19	8/29/2012	13:40:52		110	129	
20	8/29/2012	13:41:52		110	132	
21	8/29/2012	13:42:52		110	134	
22	8/29/2012	13:43:52		110	135	
23	8/29/2012	13:44:52		110	136	
24	8/29/2012	13:45:52		110	135	
25	8/29/2012	13:46:52		110	135	
26	8/29/2012	13:47:52		110	135	
27	8/29/2012	13:48:52		110	135	
28	8/29/2012	13:49:52		110	135	
29	8/29/2012	13:50:52		110	135	

Data recorded in CSV format

# Blanket & Fluid Warmers

**FHC is pleased to announce the arrival of our Smart Warmers, the most technologically advanced warmer on the market today!**

Featuring embedded data logging, alarm monitoring and LAN features with simple plug and play data downloading that requires no additional software.

## Standard Features:

- Touch-screen control
- Built-in Ethernet & Wi-fi ready
- Ease of use with help screens
- Remote monitoring & control (VNC)
- Data logging with digital signatures
- Remote tech support
- View live trends
- Text & email alarm notifications
- Alarm log
- File Transfer via USB or FTP
- Multi-level user security
- Operator audit trail
- Access from smart phone/devices
- Multi-language support (menu & help)
- Stainless steel or glass door
- Data logging of real time & temp w/ USB retrieval
- Temperature lock out
- Push button digital operation
- Large digital displays
- Displays actual temp & set points at all times
- Separate digitally controlled heating chambers
- Rapid warm time (approx. 2-6 hrs)
- Uniform heating
- Fully insulated
- Audible & visual over-temp alarm
- UL/CUL approved
- FDA registered
- OSHPD pre-approved

## Options:

- Mobile base or cart
- 18" depth
- Full recess
- Pass through chamber
- Left hand door hinge
- Keyed door lock
- Seismic brackets
- 220/240 V, 50/60HZ
- Custom sizes
- Solution baskets



FHCSWC-TS-24

# Blanket & Fluid Warmers



(FHCSWC1518-G-TL shown above)

## FHCSWC1518

**Overall Size:** 18" W x 15.5" D x 22" H

### Chamber I.D.

14" W x 13" D x 13" T  
1.4 cubic feet of storage  
Temperature range: 90-135°F  
Accuracy +/- 1°F of set point

### Electrical

120v, 3.5 amp., 50/60Hz  
.39 kw/hr, 1332 btu/hr  
UL/CUL listed  
FDA registered



(FHCSWC1824-G shown above)

## FHCSWC1824

**Overall Size:** 24" W x 20.5" D x 24.5" H

### Chamber I.D.

20" W x 17" D x 15.25" H  
3.0 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 1°F of set point

### Electrical

120v, 3.5 amp., 50/60Hz  
.45 kw/hr, 1537 btu/hr  
UL/CUL listed  
FDA registered



(FHCSWC24-G shown above)

## FHCSWC24

**Overall Size:** 30" W x 26.5" D x 24.5" H

### Chamber I.D.

26" W x 23" D x 15.25" H  
5.27 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 1°F of set point  
1 adjustable shelf

### Electrical

120v, 7.5 amp., 50/60Hz  
.30 kw/hr, 1024 btu/hr  
UL/CUL listed  
FDA registered

# Blanket & Fluid Warmers



(FHCSWC36-G shown above)

## FHCSWC36

**Overall Size:** 30" W x 26.5" D x 36" H

### Chamber I.D.

26" W x 23" D x 25" H  
8.63 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 1°F of set point  
2 adjustable shelves

### Electrical

120v, 7.5 amp., 50/60Hz  
.30 kw/hr, 1024 btu/hr  
UL/CUL listed  
FDA registered

## FHC S/S Roll-out Solution Baskets

### FHC-WRB

Our blanket warmer solution baskets are designed to provide users with the best solution warmer organization. With these warmer-safe baskets, users are able to efficiently warm solutions inside the deep pull-out baskets to make solution/fluid warming simple, easy, & organized.

(If ordered w/ warmer add -B to model #)



(FHCSWC1824-B-G shown above)

## FHC Optional Mobile Stands

**FHCT0007:** 26"W x 34"D x 34"H

Recommended for models FHCSWC24 & FHCSWC36

**FHCT0023:** 26"W x 20"D x 34"H

Recommended for models FHCSWC1518 & FHCSWC1824

(If ordered w/ warmer add -MS to model #)



**FHCT0007**

**FHCT0023**

# Blanket & Fluid Warmers



(FHCSWC2460-G shown above w/ optional mobile base)

## **FHCSWC2460**

### **Overall Size:**

24" W x 20.5" D x 64.75" H  
3 adjustable shelves

### **Chamber I.D.**

20" W x 17" D x 49.5" H  
13.05 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 3°F of set point

### **Electrical**

120v, 7.5 amp., 50/60Hz  
.49 kw/hr, 1678 btu/hr  
UL/CUL listed  
FDA registered



(FHCSWC60-G shown above w/ optional mobile base)

## **FHCSWC60**

### **Overall Size:**

30" W x 20.5" D x 64.5" H  
3 adjustable shelves

### **Chamber I.D.**

26" W x 17" D x 51" H  
13.05 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 3°F of set point

### **Electrical**

120v, 7.5 amp., 50/60Hz  
.46 kw/hr, 1570 btu/hr  
UL/CUL listed  
FDA registered

# Blanket & Fluid Warmers



(FHCSWC72-G shown above w/ optional mobile base)

## FHCSWC72

### Overall Size:

30" W x 26.5" D x 74.5" H  
2 adjustable shelves  
2 fixed shelves

### Chamber I.D.

26" W x 23" D x 61" H  
21 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 3°F of set point

### Electrical

120v, 7.5 amp., 50/60Hz  
.53 kw/hr, 1810 btu/hr  
UL/CUL listed  
FDA registered



(FHCDWC2424 shown above w/ optional mobile base)

## FHCDWC2424

### Overall Size:

24" W x 26.5" D x 74.5" H  
15.95 cubic feet of storage  
3 adjustable shelves

### Upper Chamber I.D.

20" W x 23" D x 15.25" H  
4.05 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 1°F of set point

### Lower Chamber I.D.

26" W x 23" D x 34.5" H  
11.9 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 3°F of set point

### Electrical

120v, 10 amp., 50/60Hz  
.46 kw/hr, 1570 btu/hr  
UL/CUL listed  
FDA registered

# Blanket & Fluid Warmers



(FHCDWC2460-G shown above)

## FHCDWC2460

### Overall Size:

24" W x 20.5" D x 64.75" H  
7.45 cubic feet of storage  
3 adjustable shelves

### Upper Chamber I.D.

20" W x 17" D x 13.5" H  
2.65 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 1°F of set point

### Lower Chamber I.D.

20" W x 17" D x 24.5" H  
4.80 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 2°F of set point

### Electrical

120v, 10 amp., 50/60Hz  
.49 kw/hr, 1678 btu/hr  
UL/CUL listed  
FDA registered



(FHCDWC24 shown above w/ optional mobile base)

## FHCDWC24

### Overall Size:

30" W x 26.5" D x 74.5" H  
17.2 cubic feet of storage  
3 adjustable shelves

### Upper Chamber I.D.

26" W x 23" D x 15.25" H  
5.27 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 1°F of set point

### Lower Chamber I.D.

26" W x 23" D x 34.5" H  
11.93 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 3°F of set point

### Electrical

120v, 12 amp., 50/60Hz  
.75 kw/hr, 2557 btu/hr  
UL/CUL listed  
FDA registered



# Blanket & Fluid Warmers



(FHCDWC36-G shown above w/ optional mobile base)

## FHCDWC36

### Overall Size:

30" W x 26.5" D x 74.5" H  
17.59 cubic feet of storage  
4 adjustable shelves

### Upper Chamber I.D.

26" W x 23" D x 25" H  
8.63 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 2°F of set point

### Lower Chamber I.D.

26" W x 23" D x 26" H  
8.96 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 2°F of set point

### Electrical

120v, 12 amp., 50/60Hz  
.69 kw/hr, 2356 btu/hr  
UL/CUL listed  
FDA registered



(FHCDWC60-G shown above)

## FHCDWC60

### Overall Size:

30" W x 20.5" D x 64.75" H  
9.73 cubic feet of storage  
3 adjustable shelves

### Upper Chamber I.D.

26" W x 17" D x 13.5" H  
3.46 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 3°F of set point

### Lower Chamber I.D.

26" W x 17" D x 24.5" H  
6.27 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 3°F of set point

### Electrical

120v, 7.5 amp., 50/60Hz  
.49 kw/hr, 1678 btu/hr  
UL/CUL listed  
FDA registered

# Blanket & Fluid Warmers



(FHCTWC24-G shown above w/ optional mobile base)

## FHCTWC24

### Overall Size:

30" W x 26.5" D x 78.25" H  
14.00 cubic feet of storage  
1 adjustable shelf

### Electrical

120v, 13.5 amp., 50/60Hz  
.65 kw/hr, 2238 btu/hr  
UL/CUL listed  
FDA registered

### Upper Chamber I.D.

26" W x 23" D x 11.25" H  
3.9 cubic feet of storage  
Temperature range: 90-110°F  
Accuracy +/- 1°F of set point

### Middle Chamber I.D.

26" W x 23" D x 10.75" H  
3.7 cubic feet of storage  
Temperature range: 90-135°F  
Accuracy +/- 1°F of set point

### Lower Chamber I.D.

26" W x 23" D x 18.50" H  
6.4 cubic feet of storage  
Temperature range: 90-160°F  
Accuracy +/- 1°F of set point

## Optional FHC Mobile Base:



## FHC-MB

### Overall Size:

33" W x 28" D x 6.75" H

(If ordered w/ warmer, add -MB to model #)

**Note:** Mobile base will add 2" to standard blanket warmer height.

# Blanket & Fluid Warmers

## How to order Blanket & Fluid Warming Cabinets

Options Available	18" Depth	Glass Doors	Mobile Base	Mobile Stand	Recessed Unit	LH Door Swing, Hinges on Left	Keyed Door Lock	Temperature Recorder	220/240 V, 50/60 HZ	Pass Through Chamber
Option Extension	18	G	MB	MS	R	LH	DL	TR	220	P

For Example: Model # FHCDWC24 with the 18" depth option, Glass Doors, Recessed unit, Hinges on the left, Keyed door lock, 220/240 V 50/60 HZ = Order Model # FHCDWC24-18-G-R-LH-DL-220

If you require any assistance please call us with any questions at (407) 322-3672 or toll free at 1-800-282-8644.

## Standard Models

Model #	Outside Dimensions
<b>Triple Chamber Units</b>	
FHCTWC24	30"W x 26.5"D x 78.25"T
FHCTWC24-G	30"W x 26.5"D x 78.25"T
<b>Double Chamber Units</b>	
FHCDWC24	30"W x 26.5"D x 74.5"T
FHCDWC24-G	30"W x 26.5"D x 74.5"T
FHCDWC2424	24"W x 26.5"D x 74.5"T
FHCDWC2424-G	24"W x 26.5"D x 74.5"T
FHCDWC2460	24"W x 20.5"D x 64.75"T
FHCDWC2460-G	24"W x 20.5"D x 64.75"T
FHCDWC36	30"W x 26.5"D x 74.5"T
FHCDWC36-G	30"W x 26.5"D x 74.5"T
FHCDWC60	30"W x 20.5"D x 64.75"T
FHCDWC60-G	30"W x 20.5"D x 64.75"T
<b>Single Chamber Units</b>	
FHCSWC1518	18"W x 15.5"D x 22"T
FHCSWC1518-G	18"W x 15.5"D x 22"T
FHCSWC1824	24"W x 20.5"D x 24.5"T
FHCSWC1824-G	24"W x 20.5"D x 24.5"T
FHCSWC24	30"W x 26.5"D x 24.5"T
FHCSWC24-G	30"W x 26.5"D x 24.5"T
FHCSWC2460	24"W x 20.5"D x 64.75"T
FHCSWC2460-G	24"W x 20.5"D x 64.75"T
FHCSWC36	30"W x 26.5"D x 36"T
FHCSWC36-G	30"W x 26.5"D x 36"T
FHCSWC60	30"W x 20.5"D x 64.75"T
FHCSWC60-G	30"W x 20.5"D x 64.75"T
FHCSWC72	30"W x 26.5"D x 74.5"T
FHCSWC72-G	30"W x 26.5"D x 74.5"T

**NOTE:** Due to the vast number of sizes we have available, not all of our models are shown. Please let us know your specific dimensions to get the model that will best suit your needs. If we don't currently have the size you need, we will build a custom one for you!

## Warranty

All warming cabinets manufactured by Future Health Concepts, Inc. (FHC) will carry a lifetime guarantee against product craftsmanship, **1-year labor and 5-year parts guarantee.** The factory will service all units without cost to the buyer for 1-year from shipment. After the 1-year period, replacement of a defective part (labor) will be at buyer's expense. We will exchange all defective parts at no cost to the buyer for a period of 5-years from shipment. All defective parts must be returned within 30 days to ensure proper credit. An RA from Future Health Concepts, Inc. must be obtained prior to items return.

# Blanket & Fluid Warmers

## Blanket & Fluid Warmer Storage Information:

Model #	Total Cubic Feet	# of Blankets*	# of Solution 1 Liter Bottles	# of 1/2 Liter Bottles
FHCSWC1518	1.40	1-2	9	-
FHCSWC1824	3.00	6-9	20	-
FHCSWC24	5.27	9-14	36	-
FHCSWC2460	9.73	30-40	66	-
FHCSWC36	8.63	24-30	72	-
FHCSWC60	13.05	50-65	89	-
FHCSWC72	21.00	65-85	143	-
FHCDWC24 Lower Chamber	11.93	35-50	-	-
FHCDWC2424 Lower Chamber	11.93	35-50	-	-
FHCDWC2460 Lower Chamber	4.80	14-22	-	-
FHCDWC36 Lower Chamber	8.96	24-30	-	-
FHCDWC60 Lower Chamber	6.27	12-16	-	-
FHCTWC24 Lower Chamber	6.4	12-16	-	-
30" Roll-out Basket	-	-	30	42
1824 Roll-out Basket	-	-	16	20

**\*Number of blankets will depend on thickness of blankets, positioning, and fold.**